



# AN INNOVATIVE ID CARD PRINTER TECHNOLOGY LEADER

IDP, one of the ID Card Printer industry, has been dedicated to make a better ID Card Printer with diverse and innovative approaches with its technology.

IDP, one of the pioneers of ID Card printing technology, has developed and manufactured ID card printers since 2005. We differentiate ourselves by providing high quality products with the latest mechanical, electronic and software technologies and by providing the best technical supports and warranties. Our card printers support not only graphic quality color printing and laminating but also all kinds of encodings such as magnetic stripe and contact and contactless smart card.

These printers are used for all kind of cards like employee badges, student IDs, payment cards, access control card, leisure membership cards and customer loyalty cards etc.

IDP aims at making plastic card printing widely available and affordable by offering simple, on-demand and customized printing solutions that bring quality to the largest scope of business users.

We wish you and us become good partners in this industry.













manufactured by IDP Corporation, is a highly engineered dye-sublimation ID Card printer which provides you with maximum efficiency for production of plastic cards in commercial and government applications.

SMART series is designed to support a flexible user environment, which makes it easy to choose the correct printer and save money. You can easily add a flipper or laminator, for dual sided printing or laminating, and various encoders such as magnetic stripe, contact and contactless. The enhanced FINE™ Imaging Technology of the SMART series enables you to print high quality images. The SMART Series will be a perfect choice for Employee IDs, Membership Cards, Access Control Badges, Secure Government Credentials, Social Services Cards, and even the instant issuance of Banking cards.

Please come and experience the flexibility and quality of the SMART series.



#### **TECHNOLOGY**

Clear printing by FINE™ Imaging Technology

Instant direct heating mechanism for lamination \*Patent

Field upgradable options for dual sided printing and laminating

Field upgradable encoders for magnetic stripe, contact and contactless smart card

Automatic ribbon recognition and no need for sensors & motors calibration

Eco friendly rewritable printing (SMART-31R)

500 cards & scratch free (SMART-70) \*Patent

High-durability: Metal frame & shaft, all bearing (SMART-51 & 70)

## **SOFTWARE**

SMART SDK, to develop customized applications SMART Utilities, to check working states and adjust configurations Smart ID for designing and issuing cards On-Line technical support

### **CONVENIENCE**

User friendly design for desktop environment

LCD & LED for status display of printer

Easy Thermal Print Head (TPH) replacement

Front input and output hoppers (SMART-31 & 51)

Drop-in ribbon cartridge (SMART-31 & 51)

Full modular design (SMART-70)

Drawer type ribbon cartridge (SMART-70)



Smart ID ensures appropriate card issuance and data management with SMART series printers at no extra cost. This application allows you to design and issue a desired card conveniently. It can be easily used with simple essential functions. Also, it is designed for advanced user to use a variety of detailed functions.



- Design and print (Image, Photo and Text)
- 1D & 2D Barcode printing
- Auto portrait (Auto face detection, adjustment of size & position)
- Printing of sequential numbers
- Card design templates
- Plug-in for supporting external devices (Sign pad, Camera, Scanner)
- Convenient card issuance and data management
- Magnetic stripe (MS), contact & contactless smart card encoding by using plug-in program

Smart ID is a software which is provided with Smart ID Card Printer.



SMART series provides effective security features for access control and data encryption.



- SMART series has a password verification function to provide administrator and user authentications.
- SMART series can set a specific authorized PC for encoding and printing cards.
- SMART series can encrypt data transmitted on USB and can support SSL (Secure Socket Layer) protocol on ethernet communications.
- SMART-70 series is equipped with physical lock and Kensington lock system on each station to increase security.



SMART series can utilize the network printer server for encoding and printing cards.



- SMART Ethernet module can not only print cards but also encode MS, contact and contactless smart card through the network.
- SMART Ethernet module has OCP(Open Card Print) protocol which can encode and print cards by using commands on multiple platforms without installing the printer driver.
- Available encoding the contact & contactless smart card by Ethernet.



idp-corp.com

SMARTE 70
Whatever you want or need!

## **Ultimate ID Card Printer Solution**

smart 70

is a high-performance large capacity ID card printer designed by the unique modular concept that can support various printer configurations to meet different user requirements.

500 cards can be continuously printed, laminated and encoded on various cards. SMART-70 consists of 5 different modules (Input Hopper, Printer, Hybrid Flipper, Laminator, Output Hopper) that can be configured in various combinations according to different customer requirements. Required modules can be easily added to extend functions depending on your needs.















## Easily Upgradable, No need for Tools or IT technician

## Just connect each station and synchronize



#### Input Hopper

Large Capacity
Max. 500 cards
Scratch Free
Residual Q'ty Sensor
High Durability / Indicator LED
Near empty & empty alert notifications
Physical Lock & Kensington Lock



#### • Printer

High Speed Printing

Max. 1,000 cards/h (Mono) | Max. 225 cards/h (YMCKO)

300 dpi with Edge-to-Edge Printing

Enhanced FINE™ Imaging Technology

Drawer type ribbon cartridge

Installable MS & Contactless Encoder

LCD & Button / Indicator LED

High Durability

Physical Lock & Kensington Lock



#### Hybrid Flipper

Installable Encoding modules
Contact & Contactless Smartcard Encoder
Image Scanning & Barcode Recognition
Dual Sided Image Scanning (600 / 300 dpi),
1D & 2D Barcode Recognition (Front / Back)
Card Flipper
High Durability, Indicator LED
Error Card Bin\* (Max. 30 cards)
Physical Lock & Kensington Lock



#### Laminator

No warming-up time Instant direct heating mechanism Scratch Free Drawer type film cartridge LCD & Button / Indicator LED High Durability Physical Lock & Kensington Lock



#### Output Hopper

Large Capacity
Max. 500 cards
Scratch Free
Residual Q'ty Sensor
Full space alert notifications
High Durability / Indicator LED
Physical Lock & Kensington Lock



Stacker

Max. 100 cards

\* If encoder or scanner options are not selected, Error card bin will be provided.

## **■ FLEXIBILITY**

















Single sided Printing | Single sided Printing & Laminating | Dual sided Printing, Encoding & Laminating | Single or Dual sided Multi-Printing, Laminating & Encoding | Stand-alone Laminating

## Multi - Printer Combination

**9.9** 

364 cards/hour Partial Area Printing (YMCKO)

Input Hopper +
PRINTER (YMC) + PRINTER (KO)



288 cards/hour

## Versatile Hopper



- High Volume In/Output Hopper (500 or 300 cards Cartridge Selectable)
- Multi- Hopper
- · Residual Q'ty Sensor
- Physical Lock & Kensigton Lock
- Scratch Free



## **Stand-alone** Laminator



\* For Single sided Partial area or Full area Color Printing





## **Laser Engraver for ID Cards**

SMART-70X is a laser engraver module of IDP's SMART-70 Series ID card printer.

Equipped with laser engraving capability, SMART-70X is a perfect solution for instant personalization of secure cards in an environment where the maximum level of security is required.

With the unique modular concept of SMART-70 Series,

SMART-70X can be used as a stand-alone laser engraver or with other SMART-70 modules such as SMART-70 direct-to-card printer, Laminator, Hybrid Flipper, Output hopper.

\*PC (Polycarbonate) card is recommended for standalone use of SMART-70X.
\*Laserable PVC card is recommended for use of SMART-70X with SMART-70 Printer (Dye-Sublimation Printing)

- Stand-alone single or dual-sided laser engraving (Text, Images and Security features)
- 1200dpi, Raster & Vector Scanning
- Micro Text, MRZ (Machine Readable Zone) Text
- CLI (Changeable Laser Image)
- Tactile Effect
- Magnetic encoder, contact / contactless encoder installable
- High Volume Input & Output Hopper, Color & Mono Printing (as optional modules)
- Eco-Friendly Low Power Consumption
- Full Modular Design



SMART-70 Input Hopper + SMART-70 Printer + SMART-70X Laser Engraver

#### Laser Engraving Technique









#### Flexibility

Easily Upgradable, No need for Tools or IT technician

Just connect each station and synchronize





## Ideal solution for printing high-quality ID cards in moments.

Single-sided SMART-51 (51S) can be transformed into a dual-sided printer (51D) or into dual-sided printer with laminator (51L) by applying Flipper module or Laminator module at the back of the printer which can be easily installable.

SMART-51 Laminator is a good option for printing and laminating at the same time which enables to produce extra security long-life ID cards with customizable security patch films. With DLW (Direct Laminating in a Wink) technology, SMART-51 Laminator ensures most stable & fast laminating with premium quality protection for ID cards.

- New Input Hopper (up to 200 cards loading)
- Removable Output Hopper (\*Option)
- Support of Transparent Cards
- · Cartridge type Laminate Film Loading
- · Support CR79 Cards

- · Top-side Mag. Encoding
- All-in-One type Lock System (\*Option)
- Single Card Feeder (\*Option)
- Kensington Security Lock (\*Option)
- Back-side Stacker (up to 100 cards, \*Option)







- Print Speed: Max. 17 sec./card (YMCKO)
- 300, 600 & 1200dpi with Edge-to-Edge Printing
- 2 Lines LCD with 2 LED Buttons for Front Operation
- Support of Transparent Cards
- Low Cost Security with UV Printing
- Installable Encoders: MS, Contact & Contactless
- Upgradable Modules: Flipper, Laminator & Ethernet, WiFi



smart-51 D



- Print Speed: Max. 22 sec./card (YMCKOK)
- 300, 600 & 1200dpi with Edge-to-Edge Printing
- 51S Field Upgradable to 51D
- 2 Lines LCD with 2 LED Buttons for Front Operation
- · Low Cost Security with UV Printing
- Installable Encoders: MS, Contact & Contactless
- Upgradable Modules: Laminator & Ethernet, WiFi



smart-51L

- Single or Dual Sided Printing and Laminating
- Instant Direct Heating Lamination \*patent
- Printing & Laminating Speed: Max. 22 sec./card (YMCK & Single Lamination)
- 300, 600 & 1200dpi with Edge-to-Edge Printing
- 51S & 51D Field Upgradable to 51L
- 2 Lines LCD with 2 LED Buttons for Front Operation
- Holographic Lamination for Visual Security & Card Durability
- Installable Encoders: MS, Contact & Contactless
- Upgradable Modules: Ethernet, WiFi



- Improvement of Print speed
- 300, 600 & 1200dpi Printing Resolution
- Enhanced FINE™ Imaging Technology
- State-of-the-art CPU
- Reduced Printing Noise
- All-in-one Lock system (\*Option)
- $\bullet \ {\sf Easy} \ to \ {\sf Handle} \ {\sf Laminate} \ {\sf Film} \ {\sf Cartridge}$
- Back-side Stacker (up to 100 cards, \*Option)





## Simple and Easy for everyone to use



SMART-31 Series value class ID card printer for everyone which is a perfect solution for printing ID cards at a low budget.

SMART-31S (single-sided), SMART-31D (dual-sided) and SMART-31R (rewritable) printer models are available.

SMART-31 Rewritable printer is an ideal solution for printing temporary information on ID cards.

#### **Applications**

Employee ID card
Student ID
Payment card
Health card
Leisure resort pass card
Identification card
Transport pass card
Loyalty card / Event card





- · Color & Mono Single Sided Printing
- Print Speed: Max. 23 sec./card (YMCKO)
- 300, 600 & 1200dpi with Edge-to-Edge Printing
- LED Button for Front Operation
- Low Cost Security with UV Printing
- Installable Encoders: MS, Contact & Contactless
- Upgradable Modules: Flipper & Ethernet



smart-31D

- · Single or Dual Sided Printing
- Print Speed: Max. 29 sec./card (YMCKOK)
- 300, 600 & 1200dpi with Edge-to-Edge Printing
- 31S Field Upgradable to 31D
- LED Button for Front Operation
- · Low Cost Security with UV Printing
- Installable Encoders: MS, Contact & Contactless
- Upgradable Modules: Ethernet



smart-31 R

- Direct Thermal Rewritable Method
- Rewrite Speed: Max. 12 sec./card
- 300, 600 & 1200dpi with Edge-to-Edge Printing
- LED Button for Front Operation
- Installable Encoders: MS, Contact & Contactless
- Upgradable Modules: Ethernet



# Technologies for Printer

#### Plastic card Printing



Plastic cards are prevalent in our daily lives, such as payment cards driver's licenses, membership cards and employee identification badges.

Their standard size, portability, and durability make them the ideal choice for many applications.

## Lamination



Lamination uses polyester film onto a card's surface to protect it from heat, pressure, wear, tear and to fight adhesive things.

The film is applied to card at a high temperature.

#### **UV Panel**



The UV Panel is an advanced form of panel for security that shows a fluorescence image with UV light. It is cost-effective and an easy way to protect fake cards. To prevent counterfeit, some ID cards include a UV watermark which is only visible under the UV light.

#### Encoding



Encoding is one of the important functions in ID card printer. We issue ID card not only for visual identification but for storing some information. There are three major encoding methods such as magnetic stripe, contact IC and contactless IC. IDP Card printer supplies all kinds of encoding options together with the picture quality printing.

## Smart 51 KIOSK CARD PRINTER

- · Single or Dual-sided Card Printing
- Up to 4 Selectable Hoppers
- 300 or 500 Card Refillable Cartridges
- Up to 212 cards/hour (YMCKO)
- Installable MS, Contact & Contactless Encoder
- Compact and Reliable design
- Customizable bottom plate (Size, Layout of Control Panel & Adaptor, etc.)
- SMART-51SK : Single sided ID Card Printer
- SMART-51DK : Dual sided ID Card Printer











## High capacity, flexible and reliable card printing module for various Kiosks solutions.

The IDP's Kiosk Card Printer is a high capacity, flexible and reliable card printing module for various types of self-service Kiosks.

Using the compact and solid SMART-51 printing engine or high performance SMART-70 printer module and multi-hopper system (up to 6 input hoppers) with detachable 300 or 500 cards cartridge, the IDP SMART Kiosk Card Printer will provide variety of choices depending on the requirements.

# SMERE 70 Multiple Hopper

- Multiple Hopper system designed to fit the SMART-70 Series
- Up to 6 Selectable Hoppers
- 300 or 500 Cards Refillable Cartridges
- Up to 6 Different type cards loading
- Full Metal structure



"3,000" cards loading







#### Multiple Hopper system designed to fit the SMART-70 Series.

Multiple hopper system for SMART-70 is designed to fit the needs of large capacity with high efficiency for Kiosk operation.

From minimum 2 to maximum 6 large capacity 500 cards hoppers can be used depending on the user environment. Monochrome ribbon supports up to 3000 prints minimizing maintenance cost and time and up to 3000 cards loadable hoppers with 6 different types on each hopper will maximize the efficiency of Kiosk application.

 $Advantage \ of \ SMART-70's \ unique \ full \ modular \ design \ makes \ it \ possible \ to \ add \ Encoding \ module \ and \ Laminating \ module.$ 

 $Full\ metal\ structure\ of\ the\ multiple\ hopper\ system\ is\ ideal\ for\ high\ volume\ is suance\ environment.$ 













## **Securely Destroy Sensitive Personal Information**

#### **Security Assurance**

Protecting personal information is paramount and IDP SMART-BIT shredder is specially designed to ensure the secure destruction of used ID Card Printer Ribbon with personal information.

#### Flexible Card Printer Ribbon Compatibility

The SMART-BIT is designed to accommodate the industry's popular brands of direct-to-card printer ribbons.

#### **Complete Shredding**

\* Twisted Micro-Cut Technology (Patent)

With the IDP's Twisted Micro-Cut Technology, SMART-BIT uses unique twist and cut motions to completely shred ID Card Printer ribbon panels into tiny unrecognizable particles.

#### **Compact Easy-to-use Design**

SMART-BIT is compact and light weight in design and will easily fit into any office desktop environment. The SMART-BIT's waste bag will ensure complete capture of ribbon particles and simple transfer to a waste bin.



Shredable Ribbon Type	Dye-Sublimation Ribbon, Resin & Wax Ribbon
Shredable Ribbon Width	60mm to 90mm (Installable Ribbon Core Width : Max. 120mm)
Installable Ribbon Diameter	Max. Ø 80
Shredding Speed	Max. 12 meters/minute
Shredder Bin Capacity	6 Rolls (YMCKO, 250 cards/roll)
Cutting Type	Twisted Micro Cut *Patent
Shredded Particle Size	Approx- 2-5mm
Control	Speed (Normal or Fast mode), Start & Stop, Reverse
Auto Stop	Finished Shredding, Ribbon Jam
Interface	4 LEDs, 3 Buttons
Power Supply	DC24V, 2A
Temperature / Humidity	15~35℃ / 35~70%
Dimensions (W x H x L)   Weight	232 x 364.6 x 386 mm / 9.1 x 14.4 x 15.2 inch   Approx. 4.8 kg / 10.6 lbs

#### **Complete Shredding**




With the IDP's Twisted Micro-Cut Technology, SMART-BIT uses its unique twist and cut motions to completely shred ribbon panels into tiny particles. ("Patent pending)

## Easy-to-use



Easy to use interface and shredded ribbons can be easily discarded using the SMART-BIT Waste Bag when full.

## Flexible Ribbon Compatibility



The SMART-BIT will accommodate the industry's popular brands of direct-to-card desktop printer ribbons.

#### **Compact Design**



The SMART-BIT is simple to use and has a compact size and light weight design that can easily fit into any office desktop environment.



# Retransfer class ID CARD PRINTER WISE-CXD80

- Color & Mono Single or Dual Sided Printing
- Print Speed: 29 sec./card (YMCK)
- Detachable and anytime-refillable hopper
- Intuitive and flexible function LCD panel
- Removable and water-washable cleaning roller
- Security locks on hopper & front door
- Kensington lock
- Inline encoding and lamination (with optional unit)
- Environmentally friendly compact design



WISE-CL600 Laminator WISE-CXD80 Printer

#### **Specifications**

Model		WISE-CXD80SS (Single side)	WISE-CXD80DS (Dual sides)
Printing	Print Type	Dye Sublimation / Resin Thermal Retransfer	
	Print Area	Full Bleed (Rea	al edge-to-edge)
	Resolution	300	) dpi
Card	Card Feeding	Auto	matic
	Card Size	ISO CR80 (54mm x 8	36mm / 2.12"x3.38")
	Card Thickness	0.25mm(10mil)	~ 1.0mm(40mil)
	Card Type	PVC, Compo	site PVC, PET
Print Speed	YMCK	29 sec./card (124 cards/hour) 29 sec./card (124 cards/hour)	
	YMCKK	-	40 sec./card (90 cards/hour)
Capacity	Input & Output	100 cards each(0.76mm)	
System	Supported Platform	Microsoft Windows 2000 Pro., XP, Vista, Windows Sever 2003 R2 SP2, Sever 20	
	Communication	USB2.0, Ethernet	fitted as standard
	Power Supply	Max. 3A (100V to 120V), Max. 1.5A (220V to 240V)	
	Temperature/Humidity	15~35℃,	/ 35~70%
Dimensions	Dimensions (WxLxH)	343mm (13.5") x 322mm (12.7") x 335mm (13.2")	
	Weight (kg/lbs)	13.0 / 28.7 (without optional unit)	15.5 / 34.2 (with optional unit)
Options		Magnetic stripe Encoding (HiCo/LoCo), Contact chip Encoding (Read/Write)	
		Contactless Encoding, Bend Remedy Unit, Lamination Unit (*WISE-CL600)	
Certifications		CE, FCC, KC	

Laminator for WISE Series

**WiSE-CL600** 

The superior quality of lamination printing for high security

## Print with Security



Security Erase

## High Security and Sophisticated Laser Personalization System



WISE-LE Laser Engraver

WISE-CXD80 Printer

Laser Engraver for WISE Series

## WiSE-LE

- Laser Engraver for WISE Retransfer ID Card Printer
- Single or Dual-Sided Laser Engraving of Text, Images and Security Features
- 1200dpi, Raster & Vector Scanning
- Micro Text, MRZ (Machine Readable Zone) Text
- MLI (Multiple Laser Image)
- Tactile Effect
- Color & Mono Printing (with WISE-CXD80)
- Eco-Friendly Low Power Consumption

## Consumables for **SMART-70** Series

COLOR RIBBO	NS	
YMCKO	500 Cards/Roll	Full Color Ribbon with Resin Black & Overlay
YMCKOK	500 Cards/Roll	Full Color Ribbon with Resin Black, Overlay & Black for Back Side
YMCFKO	500 Cards/Roll	Full Color Ribbon with UV Panel, Resin Black and Overlay
HYMCKO	1000 Cards/Roll	Half Panel Size Color Ribbon with Resin Black and Overlay
YMC	1000 Cards/Roll	Full Color Ribbon

MONO RIBE	BONS	
КО	1500 Cards/Roll	Black with Overlay
K	3000 Cards/Roll	Black
W	3000 Cards/Roll	White
В	3000 Cards/Roll	Blue
R	3000 Cards/Roll	Red
MG	3000 Cards/Roll	Metallic Gold
MS	3000 Cards/Roll	Metallic Sliver
S0	3000 Cards/Roll	Scratch-Off

SECURITY FILMS		
HPF	500 Cards/Roll	Hologram Patch Film
CPF	500 Cards/Roll	Clear Patch Film

## Consumables for SMART-31 & 51 Series


COLOR RIBBO	NS	
YMCKO	250 Cards/Roll	Full Color Ribbon with Resin Black & Overlay
YMCKOK	200 Cards/Roll	Full Color Ribbon with Resin Black, Overlay & Black for Back Side
YMCFKO	200 Cards/Roll	Full Color Ribbon with UV Panel, Resin Black and Overlay
НҮМСКО	350 Cards/Roll	Half Panel Size Color Ribbon with Resin Black and Overlay
ЗҮМСКО	400 Cards/Roll	1/3 Panel Size Color Ribbon with Resin Black and Overlay

MONO RIBBON	IS	
KO	600 Cards/Roll	Black with Overlay
K	1200 Cards/Roll	Black
W	1200 Cards/Roll	White
В	1200 Cards/Roll	Blue
R	1200 Cards/Roll	Red
MG	1200 Cards/Roll	Metallic Gold
MS	1200 Cards/Roll	Metallic Sliver
S0	1200 Cards/Roll	Scratch-Off

SECURITY FILMS		
HPF	250 Cards/Roll	Hologram Patch Film
CPF	250 Cards/Roll	Clear Patch Film

## **Cleaning Kits & White Card**





## **smart**-70 Printer

Printing	Print Type	Direct Dye-Sublimation
	Print Area	Edge to Edge
	Resolution	300dpi
Card	Card Feeding	Automatic
	Card Size	ISO CR80 (54mm x 86mm / 2.12" x 3.38")
	Card Thickness	0.38mm (15mil), 1.2mm (47mil)
	Card Type	PVC, Composite PVC, PET
Print Speed	Monochrome	3.6 sec./card (1,000 cards/hour)
	YMCKO	Max. 16 sec./card (225 cards/hour)
	YMCKOK	Max. 22 sec./card (164 cards/hour)
Capacity	Input Hopper: Card	500 cards
	Output Hopper: Card	Stacker: 100 cards / *Optional Output Hopper: 500 cards
System	Memory	64MB RAM
	Interface	2 Line LCD / 4 Buttons / 1 LED Indicator
	Supported Platforms	MS Windows 7/8/10, Mac OS, Linux
	Communication	USB, 2 USB Host, Ethernet
	Power	DC 24V, 2A
	Temperature/Humidity	15~35℃ / 35~70%
	Magnetic	ISO 7811 (Track I, II, III Read/ Write, HiCo/ LoCo), JIS II
Encoding	Contactless	MIFARE, ISO 14443 (Type A/B), ISO 15693, DESFIRE, ICLASS
Options	Physical Lock	Ribbon
Security	S/W	PC authentication, Password authentication
	Station Itself	Kensington Lock
	Millimeter	240 (W) x 214 (L) x 305 (H)
Dimensions	Inch	9.5 (W) x 8.4 (L) x 12 (H)
Weight	kg/lbs	Approx. 6.3 kg/13.9 lbs

 $<sup>\</sup>begin{tabular}{ll} \begin{tabular}{ll} \beg$ 

## **5mart**-70 Laminator

Laminating	Туре	Direct Heating Lamination
	Speed	19 sec./card (Single-sided Laminating)
Laminating	Туре	Clear, Holographic
Film	Thickness	0.6mil, 1.0mil
	Capacity	500 cards/Roll
System	Interface	2 Line LCD / 4 Buttons / 1 LED Indicator
	Communication	USB, RS-232C
	Power	DC 24V, 2.3A
	Temperature/Humidity	15~35℃ / 35~70%
	Physical Lock	Laminating Film
Security	Station Itself	Kensington Lock
	Millimeter	240 (W) x 214 (L) x 305 (H)
Dimensions	Inch	9.5 (W) x 8.4 (L) x 12 (H)
Weight	kg/lbs	Approx. 6.1 kg/13.4 lbs

## **smart**-70 Hybrid Flipper

	•	
Encoding Options	Contact	ISO 7816 A/B/C Card, ISO 7816 1/2/3/4 Microprocessor Card
	Contactless	ISO 14443 (Type A/B), Mifare, DEFIRE, iCLASS, ISO 18092(NFC), Felica
Scanner Options	Image Scanner	Selectable 300 & 600 dpi Dual-sided image scannig resolution,
	Scanning Speed	4.5sec/card (300 dpi), 6sec/card (600 dpi)
	Barcode Recognition	1D & 2D Barcode Recognition (Front/Back)
System	Communication	USB
	Power	DC 24V, 2A
	Temperature/Humidity	15~35℃ / 35~70%
	Physical Lock	Encoder or Error Card
Security	Station Itself	Kensington Lock
	Millimeter	110 (W) x 204 (L) x 305 (H)
Dimensions	Inch	4.3 (W) x 8.0 (L) x 12 (H)
Weight	kg/lbs	Approx. 2.8 kg/6.2 lbs. (Without Optional modules)
Error Card Bin Ejection device for faulty card is equipped inside Flipper (Max. 30 cards)		* If encoder or scanner options are not selected, Error Card Bin will be provided.

## **SM∃**FE-70 Input/Output Hopper

Capacity	Input / Output	500 or 300 cards Cartridge Selectable
	Feeding	Automatic
Card	Size	ISO CR80 (54mm x 86mm / 2.12" x 3.38")
	Thickness	0.38mm (15mil), 1.2mm (47mil)
	Туре	PVC, Composite PVC, PET
Sensor	Residual Q'ty Sensor	Input: Near Empty & Empty / Output: Full Space
	Detection Sensor	Cartridge Mount Status Detectable
System	Communication	USB, RS-232C
	Power	DC 24V, 2A
	Temperature/Humidity	15~35℃ / 35~70%
Security	Physical Lock	Cartridge
	Station Itself	Kensington Lock
Dimensions	Input Hopper (WxLxH)	170 x 204 x 548 mm / 6.7 x 8.0 x 21.6 inch
	Output Hopper (WxLxH)	149 x 204 x 548 mm / 5.9 x 8.0 x 21.6 inch
Weight	Input Hopper (kg/lbs)	Approx. 3.7 kg /8.2 lbs
	Output Hopper (kg/lbs)	Approx. 3.5 kg/7.6 lbs



## **5marb** - **51** & **31** Series

Model		Standard Class			Value Class				
		SMART-51S	SMART-51D	SMART-51L	SMART-31S	SMART-31D	SMART-31R		
			Single Sided	Dual Sided	Dual Sided & Laminator	Single Sided	Dual Sided	Rewritable	
Printing	Print Type			Dye-Sublimation	1	Dye-Su	olimation	Thermal Transfer	
	Print Area		Edge to Edge					I	
	Resolution		300dpi (Color & Mono), 600 & 1200dpi (Mono only)			300dpi (Color & Mono), 600 & 1200dpi (Mono only)			
	Dual Side Printing		Option (with Flipper)	Yes	Yes (Flipper Installed)	Option (with Flipper)	Yes	No	
Card	Card Feeding				Autor	matic			
	Card Size		ISO CR80 or ISO CR79 (Option-Factory installed)			ISO CR80			
	Card Thickness		0.38mm (15mil), 1.0mm (40mil)			0.38mm (15mil), 0.76mm (30mil)			
	Card Type		PVC, PET, Composite PVC	PVC, PET, Composite PVC	PVC, PET, Composite PVC	PVC, PET, Composite PVC	PVC, PET, Composite PVC	Rewritable Thermochromic Material	
Print Speed	Monochrome		5 sec./card (720 cards/hour)	5 sec./card (720 cards/hour)	5 sec./card (720 cards/hour)	5 sec./card (720 cards/hour)	5 sec./card (720 cards/hour)	Max. 12 sec./card (300 cards/hour	
	УМСКО		Max. 17 sec./card (212 cards/hour)	Max. 17 sec./card (212 cards/hour)	Max. 17 sec./card (212 cards/hour)	Max.23 sec./card (156 cards/hour)	Max. 23 sec./card (156 cards/hour)	-	
	YMCKOK		-	Max. 22 sec./card (164 cards/hour)	Max. 22 sec./card (164 cards/hour)	-	Max. 29 sec./card (124 cards/hour)	-	
Laminating	Mode		-	-	Single & Dual	-	-	-	
	Film (Clear & Holographic)		-	-	0.6mil, 1.0mil	-	-	-	
	Speed	Simultaneous	-	-	22 sec./card (YMCK)	-	-	-	
		(Single Lamination)	-	-	32 sec./card (YMCKK)	-	-	-	
		One by One	-	-	43 sec./card (YMCK)	-	-	-	
		(Single Lamination)	-	-	53 sec./card (YMCKK)	-	-	-	
Capacity	Input Hopper: Card		100 Cards / 200 Cards with cover open			80			
	Output Hopper: Card		Front: 40 Cards / Rear: 100 Cards (Optional Rear-side Stacker) 25						
System	Memory		64MB RAM						
	Display		2 Line LCD			-			
	Control Panel		2 LED Buttons			1 LED Button			
	Supported Platforms		Microsoft Windows 7/ 8/10, Mac OS, Linux						
	Communication		USB / Ethernet, WiFi (Option)			USB / Ethernet (Option)			
	Power Supply		DC 24V						
	Power Consumption		48	48	96	48	48	48	
	Temperature/Humidity				15~35℃,	/ 35~70%			
Dimensions	Millimeter (WxLxH)		165 x 390 x210	165 x 498 x 210	165 x 675 x 210	172 x 377 x 190	172 x 472 x 190	172 x 377 x 190	
	Inch (WxLxH)		6.5 x 15.4 x 8.3	6.5 x 19.6 x 8.3	6.5 x 26.6 x 8.3	6.8 x 14.8 x 7.5	6.8 x 18.6 x 7.5	6.8 x 14.8 x 7.5	
Weight	Kg/lbs		4.5 / 10	5.2 / 11.5	8.8 / 19.4	3.4 / 7.5	4.2 / 9.5	3.4 / 7.5	
Encoding Options	Magnetic		ISO 7811 (Track I, II, III Read/ Write, HiCo/ LoCo), JIS II						
	Contact		ISO 7816 (ID-1)						
	Contactless		MIFARE, ISO 14443 (Type A/B), ISO 15693, DESFIRE, ICLASS						
Certifications	Certifications		CB, CE, FCC, KC, CCC CB, CE, FCC, KC, CCC						

## smart-70X & WiSE-LE

Model		SMART-70X	WISE-LE			
Laser Engraving	Laser Type	6W Air-Cooled DPSS Laser, ND:YAG				
	Resolution	1200dpi				
	Scanning	Raster & Vector Scanning				
	Engraving Mode	Single or Dual-sided Laser Engraving				
	Speed	103 cards/hour (Single-sided Laser engraving only)				
	Warranty	20,00	0,000 hours			
Card	Card Feeding	Automatic, Manual				
	Card Size	ISO CR80 (54mm x 86mm / 2.12"x 3.38")				
	Card Thickness	0.76mm (30mil)				
	Card Type	Laserable PVC, PC (Polycorbonate) Card				
Capacity	Input Hopper	Max. 500 Cards (Optional : SMART-70 Input Hopper)	-			
	Output Hopper	Max. 500 Cards (Optional : SMART-70 Output Hopper)	-			
	Error Card Bin	Max. 2	20 Cards			
System	Display	LCD & LED	LCD & LED			
	Control Panel	4 Buttons	4 Buttons			
	Vision Camera	Laser Engraving Monitoring				
	Supported Platforms	Microsoft Windows 7/ 8/ 10				
	Communication	USB				
	Power Supply	100V to 2	100V to 220V ±10%			
	Temperature/Humidity	10~30°C	7 / 20~80%			
Security	Physical Lock	Laser System, Error Card Bin				
Options	Magnetic	ISO 7811 (Track I, II, III Read/ Write, HiCo/ LoCo), JIS II	-			
	Contact	ISO 7816 A/B/C Card, ISO 7816 1/2/3/4 Microprocessor Card	-			
	Contactless	MIFARE, ISO 14443 (Type A/B), ISO 15693, DESFIRE, ICLASS	-			
	CLI (Changeable Laser Image)	Yes	-			
	MLI (Multiple Laser Image)	-	Yes			
Dimensions	Millimeter (WxLxH)	450 x 230 x 425	246 x 447 x 516			
	Inch (WxLxH)	17.7 x 9.1 x 16.7	9.7 x 17.6 x 20.3			
Weight	Weight	Approx. 25 kg (55 lbs)	Approx. 25 kg (55 lbs)			
Laser Safety	IEC-60825-1 CLASS 1 Standard					

 $<sup>{}^{\</sup>star}\textbf{Print Speed}: \textbf{May change under specific condition}.$ 

Specifications and availability may change without notice.

## **IDEAL SOLUTION FOR PRINTING HIGH-QUALITY ID CARDS IN MOMENTS**













HIGH SECURITY



HIGH SPEED PRINTING







POWERFUL NETWORKING





## IDP Corp., Ltd.

#601, 50, Digital-ro 33-gil, Guro-gu, Seoul, Korea, 08377

T +82-2-6099-3700

F +82-2-6099-3717

E sales@idp-corp.com

#### IDP Americas, Inc.

200 Circuit Drive, North Kingstown, RI 02852 U.S.A.

T +1-401-400-7111

F +1-401-667-7445

E sales.na@idpnorthamerica.com

#### **IDP Middle East**

13F, Jafza View 18, Downtown Jebel Ali P.O.Box 17588, Dubai U.A.E.

T +971-4-889-5900

E mea@idp-corp.com

www.idp-corp.com









