



WRR-44 LONG-RANGE RECEIVER



Ranger[®] Long-Range



Frequency: 433 MHz
Read Range: Up to 200 feet (61 m)



MAXSecure[™]
Unique Security Feature



ETL Listed
Independently Tested and Certified to Conform to UL Standard 294



Warranty
One-Year Warranty



Wiegand
Output Interface



U.S. or European Wall-Box Mount
Box & Flat Surfaces

WRR-44 LONG-RANGE RECEIVER

Ranger from Farpointe Data sets the electronic security benchmark for high frequency, long-range identification Receivers and Transmitters. Based upon proven contactless digital ultra high frequency (UHF) technology, the Ranger Receivers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and up to 200 feet of read range (WRR-44). Additionally, Ranger Transmitters are active devices, powered by the most reliable and common battery, and equipped with a potted proximity or contactless smartcard module. The modules can be ordered to support several proximity reader technologies and allow the Transmitter to be used as a close-range credential.

Specifications	WRR-44
Technology	Long range
Frequency	433 MHz
Mounting ¹	USA/European wall box or any flat surface
Dimensions	3.4" W × 6.3" H × 2.3" D (86.4 mm × 160 mm × 58.4 mm)
Transmission	Rolling code + encryption
Weight	12 oz (340 g)
Certifications	FCC, ICC, CE, UL Standard 294 ²
IP Code ³	IP65
Voltage ⁴	12 VDC nominal
Current Draw	120 mA typical @ 12 VDC
Read Range ⁵	Up to 200 feet (61 m), installer adjustable
Cabling ⁶	24 AWG minimum, multiconductor stranded with an overall foil shield
Interface ⁷	Wiegand (26 bit industry standard and custom Wiegand formats)
Operating Temperature	-40° F to 149° F (-40° C to +65° C)
Enclosure Color	Off-white plastic enclosure with black label
Audio Tone	Beeper included standard, installer switchable
Indoor & Outdoor Installation	Electronics sealed in a weather-resistant, UL listed enclosure
Warranty	12 months
LED	Four-state standard (red, green, amber, and off), installer switchable, as well as Power (blue) and Channel (green)
Transmitters Supported	WRT-2+ (all variants) WRT-4+ (all variants)

NOTES:

- Receiver includes a drill template providing mounting provisions to USA or European wall boxes, and pre-drilled holes in the four corners allowing installation to any flat surface. Mounting to metal may affect read range.
- Carrying the ETL Label and tested by Intertek, conforms to UL Standard 294.
- Self evaluated.
- Linear power supplies are recommended for best operation.
- Rotate read range dial on the receiver to adjust. Receiver range covers a 360-degree radius and does not need to be installed in line-of-sight to the Transmitters to function. Read range can be extended using a separate dipole antenna attached to Receiver's on-board SMA connector.
- For example, Belden 9540 or similar, wiring to a 10-Pin pluggable terminal block.
- Supports four channels per Receiver, supporting Transmitter buttons 1, 2, 3, and 4.



Farpointe Data reserves the right to change specifications without notice.

© 2012-2019 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, Ranger®, and CONEKT® are the registered U.S. trademarks of Farpointe Data, Inc. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.
 2195 Zanker Road
 San Jose, CA 95131 USA
 Office: +1-408-731-8700
 Fax: +1-408-731-8705
 support@farpointedata.com



www.farpointedata.com