

OU75 Tech Specs

OU 75 (OEM Iris Camera Module)	
Dimensions (WxHxD)	TBD
Weight	TBD
Power Input/ Consumption	12 VDC, 2.0 Amps @ 12 VDC / 15 W MAX
Iris Operating Range Indicator	None
Voice Indication	Available by download
Iris Capture Range	Minimum 200 pixels/cm Iris in Operating Range (750 ±250mm)
Flash	None
Face Image Camera	None
Operating Temperature	r 0°C~45°C (32°F~113°F)
Storage Temperature	-20°C~95°C (-4°F~203°F)
Humidity	Up to 90% non-condensing
Iris Camera Mounting	Provided by OEM
Communications	USB

Equipment Supplied with OU75	Instruction Manual – Quick Start Guide
iData SDK	OU75 Device Control SDK license
Power Supply Optional	iCAM 7 PWR
Certifications	CE, FCC, KC, Eye Safety, ISO Standard, KISA

Items Required for Use of This Product

Required Equipment (not provided by Iris ID)

- Windows based PC (Windows 7 (32/64-bit) / Windows 10 (32/64-bit))

Minimum Computer requirements

- Microsoft Windows 7 (32-bit), or Windows 7 (64-bit) OS
- 512MB RAM (or higher)
- x86 Processor, 2.0 GHz (or higher)
- 2GB available HDD space or above
- Microsoft .NET Framework ver. 3.5
- Mouse, SVGA Monitor, Keyboard
- Dedicated USB 2.0 port (or higher)
- 10/100 Base-T Ethernet Port

NOTE : An available and dedicated USB 2.0 compliant port is needed to properly use the OU75