

All-in-One POS System

AP-6715 / AP-6815



Features

- 15 inch spill proof full-flat touch screen LCD monitor
- Integrated peripherals for easy installation: receipt printer /MSR / i-Button
- Space saving, easy access to hard disk drive for improved maintenance
- Energy / performance CPU available (Core i3 / i5 / i7)
- Versatile I/O supported: USB3.0 / USB2.0 / RJ-45 / RJ11



Specifications

Model Name	AP-6715	AP-6815
Main System		
Chipset	Intel® H110	
Processor	6th Generation Sky Lake Intel® Celeron 3900TE (2.3GHz, Dual Core, 2M Cache) Intel® i3-6100TE (2.7GHz, Dual Core, 4M Cache) Intel® i5-6500TE (3.3GHz, Quad Core, 4M Cache) Intel® i7-6700TE (3.4GHz, Quad Core, 8M Cache)	7th Generation Kaby Lake Intel® Celeron G3930TE (2.7GHz, Dual Core, 2M Cache) Intel® i3-7101TE (3.4GHz, Dual Core, 4M Cache) Intel® i5-7500T (3.3GHz, Quad Core, 4M Cache) Intel® i7-7700T (3.8GHz, Quad Core, 8M Cache)
Memory	2 x DDR4 SODIMM, up to 32GB	
Storage	1 x 2.5" SATA BAY	
LCD Panel	15-inch TFT LCD with LED Backlight 1024 (W) RGB x 768(H)	
Touch Panel	True-Flat Projected Capacitive Multi Touch	
Audio	1 x 2W High Quality Speaker	
I/O Expansion		
USB	4 x USB 3.0 Type A (I/O Bracket) and 2 x USB 2.0 (Panel Side) Option : 2 x USB 2.0 (I/O Bracket)	
LAN	2 x RJ45 10/100/1000Mbps Giga Ethernet	
COM	2 x COM (DB9) and 2 x COM (RJ45), w/RI/5V/12V selectable by BIOS	
LPT	1 x DB25 Parallel Port (Option)	
HDMI	1 x HDMI	
Audio	1 x Line-out	
Cash Drawer	1 x RJ11 port supports 2 cash drawers with 12V or 24V	
DC Power Out	1 x +12V Power Output	
DC Power In	1 x Standard Mini-DIN 4PIN type	
Integrated Peripheral		
Thermal Printer	3" Thermal Printer with cutter, 203 dpi and 250 mm/s supported	
Power Management		
Power Adapter	12V@7.5A 90W Adapter (System) 24V@2.5A 60W Adapter (Printer)	
Mechanical & Environmental		
Tilt Adjustment	Fixed 50 Degree	
Dimension	374 (W) x 346 (D) x 280 (H) (mm)	
Weight	8.5 kg (with Printer)	
Certification	CE/FCC	
Operation System	POS Ready 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux (Ubuntu)	Windows 10.1 IoT
Operation Condition	0°C to +40°C / 20 to 80% without condensation (Equipped with HDD)	
Storage Condition	-20°C to +60°C / 20 to 85% without condensation	
Optional Peripheral		
2nd Display	8" (800 x 600), 9.7" (1024 x 768) and 10.1 (1280 x 1080) LCD Display, Option : PCAP Touch Panel	
Customer Display	VFD and LCD Customer Display	
MSR	Bi-directional, Comply with ISO 7811 and Three Track support	
Wi-Fi	Wi-Fi IEEE 802.11 a/b/g/n/ac	
i-Button	Dallas i-button Reader	

